# QUAD Series

# SafeStreams<sup>®</sup>

FLEXIBLE & RESILIENT CELLULAR CONNECTIVITY



The QUAD Series is a range of external 3G/4G-LTE cellular transmission solutions increasing dramatically the signal resiliency in critical conditions for live video transmission. The QUAD Series is designed to be used in combination with AVIWEST'S PRO Series, RACK series or AIR series transmission devices, as well as HE4000 UHD encoder in order to add, extend or remotely-locate transmission capacities over cellular networks. The QUAD Series portfolio includes two solutions: QUAD Antenna and QUAD CellLink.

Suitable for/or better transmission in constraints and hostile environments, the QUAD Antenna is a cellular antenna array combining 4 patented high efficiency wideband antennas. It is designed to externalize the embedded native antennas from the PRO Series or simply add transmission capability to the RACK Series.

The QUAD CellLink embeds 4 last-generation 3G/4G-LTE cellular modems with their SIM cards and inherits of the QUAD Antenna innovative technology. This agnostic solution can be combined with the HE4000 and AIR Series respectively, or any other vendor devices.

Really easy-and-fast to setup, the QUAD Series definitely facilitates video professional operations for news gathering and field events broadcasting compared to the traditional satellite-based solutions. QUAD Series enhances their excellence of services with a better video quality, a lower latency and an error free transmission.

## USE CASES

	Vehicle	Mounting Location	Magnets	M4-threaded silentblocs	1/4-20-threaded mount
Motorbike		Top case		•	
		Mast		•	
Car/Truck		Horizontal flat roof top	•	•	
Helicopter	3	Lower part of the cabin		•	
Boat		Conductive flat desk		•	
		Mast		•	
Tripod		Mounting head or magic arm		٠	٠



# **QUAD Antenna** SPECIFICATIONS

### ANTENNA

4 x wideband patented high efficiency antennas array Operating range from 600MHz to 3GHz

#### **RF PERFORMANCES**

Free Space Return Loss per antenna 1710-2700MHz < -10dB Free Space Peak Gain per antenna 700-2700MHz up to 5.4dBi

#### MOUNTING

- 4 x anti-slip magnetic pads (comply with XP ISO/PAS 11154 for mounting
- on vehicle rooftop) 1 x anti-rotation 1/7-20 threaded stud mount 4 x M4 threaded silentblocs

#### INTERFACES

Up to 9 meters cable with x4 MCX termination

#### PHYSICAL

DIMENSIONS (W x H x D)	22,2 cm x 7,9 cm x 22,2 cm [8.74" x 3.11" x 8.74"]
WEIGHT	1.4 Kg / 3.08 lbs
OPERATION TEMPERATURE	-40°C to 85°C (-40°F to 185°F)
INGRESS PROTECTION	IP65

## **QUAD CellLink** SPECIFICATIONS

4 x 3G/4G-LTE modems with patented high efficiency antennas

#### NETWORK CONNECTIONS

CELLULAR

## MOUNTING

4 x anti-slip magnetic pads (comply with XP ISO/PAS 11154 for mounting on vehicle rooftop) 1 x anti-rotation 1/7-20 threaded stud mount

Worldwide standards coverage

## INTERFACES

1 x USB 2.0 (male type-A with 3 meters cable) 4 x micro SIM slots

<b>۲</b> • 1	1.1.1		
U		<b>.</b> .	
			_

POWER SUPPLY DC input 12V-48V CONSUMPTION 25 W (max)

## PHYSICAL

DIMENSIONS (W x H x D)	22,2 cm x 9,9 cm x 22,2 cm [8.74" x 3.90" x 8.74"]
WEIGHT	2 Kg / 4.4 lbs
OPERATION TEMPERATURE	0°C to 40°C (32°F to 104°F)
INGRESS PROTECTION	IP65

# SYSTEM OVERVIEW



